



Bearing No. NJ 2313 ECPH

s	4.7 mm
d	65 mm
D	140 mm
B	48 mm
F	82.5 mm
s max.	4.7 mm
Size (mm)	140x65x48
Width (mm)	48
Mass bearing	3.36 kg
$d_1$	90.5 mm
$D_1$	117.4 mm
Limiting speed	6000 r/min
Bearing number	NJ 2313 ECPH
Reference speed	5300 r/min
Limiting value e	0.3
$d_a$ min.	77 mm
Bore Diameter (mm)	140
$D_a$ max.	127.8 mm
$d_b$ min.	93 mm
$r_a$ max.	2 mm
$d_a$ max.	80 mm
Axial load factor Y	0.4
Outer Diameter (mm)	65
$r_a$ - max.	2 mm
$D_a$ - max.	127.8 mm
$d_a$ - min.	77 mm
$r_{3,4}$ min.	2.1 mm
$d_b$ - min.	93 mm
$d_a$ - max.	80 mm
$r_{1,2}$ min.	2.1 mm

$d_1$ ?	90.5 mm
$D_1$ ?	117.4 mm
$r_{3,4}$ - min.	2.1 mm
$r_{1,2}$ - min.	2.1 mm
Basic dynamic load rating C	285 kN
Basic dynamic load rating - C	285 kN
Fatigue load limit $P_u$	38 kN
Calculation factor $k_r$	0.25
Calculation factor - $k_r$	0.25
Fatigue load limit - $P_u$	38 kN
Basic static load rating $C_0$	290 kN
Basic static load rating - $C_0$	290 kN