




Bearing No. S7203 ACD/P4A

D	40 mm
d	17 mm
B	12 mm
a	12.8 mm
Ball - z	10
Size (mm)	40x17x12
Width (mm)	12
Mass bearing	0.065 kg
D ₂	34.4 mm
d ₂	24.1 mm
d ₁	24.1 mm
d ₂	24.1 mm
D ₂	34.4 mm
d ₁	24.1 mm
Bearing number	S7203 ACD/P4A
Preload class B	68 N/micron
Preload class A	53 N/micron
Preload class D	118 N/micron
Preload class C	89 N/micron
Number of balls z	10
r _b max.	0.3 mm
r _a max.	0.6 mm
D _b max.	37.6 mm
D _a max.	35.8 mm
d _b max.	23.5 mm
d _b min.	21.2 mm
d _a max.	23.5 mm
Bore Diameter (mm)	40
d _a min.	21.2 mm
Outer Diameter (mm)	17

d_a - max.	23.5 mm
d_a - min.	21.2 mm
Calculation factor e	0.68
Calculation factor f	1.03
d_b - max.	23.5 mm
D_b - max.	37.6 mm
r_a - max.	0.6 mm
r_b - max.	0.3 mm
d_b - min.	21.2 mm
$r_{3,4}$ min.	0.3 mm
$r_{1,2}$ min.	0.6 mm
Ball - D_w	7.144 mm
D_a - max.	35.8 mm
$r_{3,4}$ - min.	0.3 mm
$r_{1,2}$ - min.	0.6 mm
Calculation factor - f	1.03
Calculation factor - e	0.68
Ball diameter D_w	7.144 mm
Basic dynamic load rating C	8.84 kN
Preload class A G_A	60 N
Basic dynamic load rating - C	8.8 kN
Preload class B G_B	120 N
Preload class C G_C	240 N
Preload class D G_D	480 N
Preload class B - G_B	120 N
Preload class C - G_C	240 N
Preload class A - G_A	60 N
Preload class D - G_D	480 N
Calculation factor f_1	0.99
Fatigue load limit P_u	0.17 kN

Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.01
Calculation factor f_{2C}	1.02
Calculation factor f_{2D}	1.05
Calculation factor f_{HC}	1
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.17 kN
Calculation factor - Y_0	0.76
Calculation factor - f_1	0.99
Calculation factor - f_{HC}	1
Calculation factor - f_{2D}	1.05
Calculation factor - f_{2C}	1.02
Calculation factor - f_{2B}	1.01
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	38000 r/min
Basic static load rating C_0	4 kN
Static axial stiffness, preload class D	118 N/ μ m
Attainable speed for grease lubrication	38000 r/min
Static axial stiffness, preload class C	89 N/ μ m
Static axial stiffness, preload class B	68 N/ μ m
Static axial stiffness, preload class A	53 N/ μ m
Basic static load rating - C_0	4 kN

Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back- to-back, face-to-face) Y_1	0.92
Calculation factor (back- to-back, face-to-face) Y_2	1.41
Calculation factor (back- to-back, face-to-face) Y_0	0.76
Calculation factor (back- to-back, face-to-face) X_2	0.67