



Bearing No. FYTBK 20 WD

J	90 mm
N	12.3 mm
d	20 mm
A	29.5 mm
T	45.6 mm
L	60.5 mm
H	12.3 mm
Size (mm)	20x29.5x15
Width (mm)	15
D _b	59 mm
A ₁	15 mm
A ₃	3.2 mm
A ₅	18.5 mm
s ₁	26.6 mm
B ₁	43.7 mm
D _b	59 mm
D _a	50.8 mm
B ₄	4.75 mm
B ₁	43.7 mm
A ₅	18.5 mm
B ₄	4.75 mm
A ₁	15 mm
s ₁	26.6 mm
Bearing number	FYTBK 20 WD
Limiting speed	1800 r/min
Housing material	Composite
Mass bearing unit	0.27 kg
Bore Diameter (mm)	20
Outer Diameter (mm)	29,5

D _a - H11	50.8 mm
A ₃ - H14	3.2 mm
Thread - G ₂	M6x0.75
Basic dynamic load rating C	12.7 kN
Basic dynamic load rating - C	12.7 kN
Thread grub screw G ₂	M6x0.75
Fatigue load limit P _u	0.28 kN
Fatigue load limit - P _u	0.28 kN
Hexagonal key size for grub screw N	3 mm
Hexagonal key size for grub screw - H	3 mm
Basic static load rating C ₀	6.55 kN
Basic static load rating - C ₀	6.6 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in