



Bearing No. NJ 2308 ECPH

s	2.9 mm
d	40 mm
D	90 mm
B	33 mm
F	52 mm
s max.	2.9 mm
Size (mm)	90x40x33
Width (mm)	33
Mass bearing	0.95 kg
d ₁	57.5 mm
D ₁	75 mm
Limiting speed	9500 r/min
Bearing number	NJ 2308 ECPH
Reference speed	8000 r/min
Limiting value e	0.3
d _a min.	48 mm
Bore Diameter (mm)	90
D _a max.	81.8 mm
d _b min.	60 mm
r _a max.	1.5 mm
d _a max.	50 mm
Axial load factor Y	0.4
Outer Diameter (mm)	40
r _a - max.	1.5 mm
D _a - max.	81.8 mm
d _a - min.	48 mm
r _{3,4} min.	1.5 mm
d _b - min.	60 mm
d _a - max.	50 mm
r _{1,2} min.	1.5 mm

d_1 ?	57.5 mm
D_1 ?	75 mm
$r_{3,4}$ - min.	1.5 mm
$r_{1,2}$ - min.	1.5 mm
Basic dynamic load rating C	129 kN
Basic dynamic load rating - C	129 kN
Fatigue load limit P_u	15.3 kN
Calculation factor k_r	0.25
Calculation factor - k_r	0.25
Fatigue load limit - P_u	15.3 kN
Basic static load rating C_0	120 kN
Basic static load rating - C_0	120 kN