



Bearing No. NJ 2219 ECP

F	112.5 mm
s	3 mm
d	95 mm
D	170 mm
B	43 mm
Bore	3.74 Inch 95 Millimeter
Noun	Bearing
Width	1.693 Inch 43 Millimeter
s max.	3 mm
UNSPSC	31171547
Profile	Complete with Outer and Inner Ring
series:	NJ22
flanges:	(2) Outer Ring, (1) Inner Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Separable	Inner Ring - One Side
Size (mm)	170x95x43
Inventory	0.0
Snap Ring	No
Width (mm)	43
bore type:	Straight
Bore Profile	Straight
Mass bearing	3.93 kg
Weight / LBS	8.814
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
maximum rpm:	4800 RPM

closure type:	Open
Product Group	B04144
Cage Material	Polymer
Inch - Metric	Metric
D ₁	147.4 mm
d ₁	120 mm
bore diameter:	95 mm
overall width:	43 mm
cage material:	Polyamide
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
fillet radius:	2 mm
Relubricatable	Yes
Bearing number	NJ 2219 ECP
Limiting speed	4800 r/min
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
number of rows:	1
finish/coating:	Uncoated
Reference speed	4300 r/min
Manufacturer URL	http://www.skf.com
Outside Diameter	6.693 Inch 170 Millimeter
Long Description	95MM Bore; Straight Bore Profile; 170MM Outside Diameter; 43MM Width; Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C0-Medium Inte

Limiting value e	0.3
ring separation:	Separable Ring
precision rating:	RBEC 1 (ISO Class Normal)
bearing material:	Steel
outer ring width:	43 mm
Weight / Kilogram	4.002
Manufacturer Name	SKF
outside diameter:	170 mm
Bore Diameter (mm)	170
Internal Clearance	C0-Medium
d _a min.	107 mm
d _a max.	110 mm
D _a max.	157.8 mm
r _a max.	2 mm
d _b min.	123 mm
Outer Diameter (mm)	95
Axial load factor Y	0.4
internal clearance:	C0
r _{3,4} min.	2.1 mm
r _{1,2} min.	2.1 mm
d _a - min.	107 mm
D _a - max.	157.8 mm
Minimum Buy Quantity	N/A
r _a - max.	2 mm
d _a - max.	110 mm
d _b - min.	123 mm
static load capacity:	375 kN
d ₁ ?	120 mm
D ₁ ?	147.4 mm
r _{3,4} - min.	2.1 mm
Harmonized Tariff Code	8482.50.00.00
	2.1 mm

r^{1,2} - min.

--	--

dynamic load capacity:	325 kN
Manufacturer Item Number	NJ 2219 ECP
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	325 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	325 kN
Fatigue load limit P_u	45.5 kN
Calculation factor k_r	0.2
Fatigue load limit - P_u	45.5 kN
Calculation factor - k_r	0.2
Basic static load rating C_0	375 kN
Basic static load rating - C_0	375 kN