

Bearing No. W 61803 R

| | |
|-----------------------------------|--------------|
| D | 26 mm |
| d | 17 mm |
| B | 5 mm |
| C | 1,1 mm |
| D3 | 28 mm |
| Weight | 0,008 Kg |
| Size (mm) | 17x26x5 |
| Width (mm) | 5 |
| Mass bearing | 0.008 kg |
| D ₃ | 28 mm |
| Limiting speed | 34000 r/min |
| Bearing number | W 61803 R |
| Reference speed | 56 000 r/min |
| r _a max. | 0.3 mm |
| d _a min. | 19 mm |
| Bore Diameter (mm) | 17 |
| Outer Diameter (mm) | 26 |
| r _{1,2} min. | 0.3 mm |
| d ₂ ? | 18.8 mm |
| D ₂ ? | 24.15 mm |
| Fatigue load limit (Pu) | 0,054 |
| Basic dynamic load rating C | 1.78 kN |
| Basic static load rating (C0) | 1,27 kN |
| Basic dynamic load rating (C) | 1,78 kN |
| Fatigue load limit P _u | 0.054 kN |
| Calculation factor k _r | 0.02 |
| Calculation factor f ₀ | 14.1 |
| Basic static load rating | 1.27 kN |

| | |
|----------------|--|
| C ₀ | |
|----------------|--|