



Bearing No. NJ 214 ECJ

F	83.5 mm
s	1.2 mm
d	70 mm
D	125 mm
B	24 mm
Bore	2.756 Inch 70 Millimeter
Noun	Bearing
Width	0.945 Inch 24 Millimeter
UNSPSC	31171547
s max.	1.2 mm
series:	NJ2
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring, (1) Inner Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
Size (mm)	125x70x24
Snap Ring	No
Separable	Inner Ring - One Side
Inventory	0.0
bore type:	Straight
Width (mm)	24
maximum rpm:	6300 RPM
Weight / LBS	2.687
Bore Profile	Straight
Mass bearing	1.18 kg
closure type:	Open
Product Group	B04144

d ₁	89.4 mm
Cage Material	Steel
D ₁	108.3 mm
Inch - Metric	Metric
Bearing number	NJ 214 ECJ
Relubricatable	Yes
fillet radius:	1.5 mm
cage material:	Steel
Limiting speed	6300 r/min
bore diameter:	70 mm
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
overall width:	24 mm
finish/coating:	Uncoated
number of rows:	1
Reference speed	6000 r/min
Precision Class	RBEC 1 ISO P0
Rolling Element	Cylindrical Roller Bearing
Long Description	70MM Bore; Straight Bore Profile; 125MM Outside Diameter; 24MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C0-Medium Intern
Limiting value e	0.2
Manufacturer URL	http://www.skf.com
ring separation:	Separable Ring
Outside Diameter	4.921 Inch 125 Millimeter

Weight / Kilogram	1.22
precision rating:	Not Rated
outside diameter:	125 mm
Manufacturer Name	SKF
outer ring width:	24 mm
bearing material:	Steel
r _a max.	1.5 mm
d _a min.	79 mm
d _a max.	81 mm
d _b min.	92 mm
D _a max.	115.4 mm
Bore Diameter (mm)	125
Internal Clearance	C0-Medium
Axial load factor Y	0.6
internal clearance:	C0
Outer Diameter (mm)	70
r _{1,2} min.	1.5 mm
r _{3,4} min.	1.5 mm
r _a - max.	1.5 mm
Minimum Buy Quantity	N/A
D _a - max.	115.4 mm
d _a - min.	79 mm
d _b - min.	92 mm
d _a - max.	81 mm
static load capacity:	137 kN
d ₁ ?	89.4 mm
D ₁ ?	108.3 mm
Harmonized Tariff Code	8482.50.00.00
r _{1,2} - min.	1.5 mm
dynamic load capacity:	137 kN
r _{3,4} - min.	1.5 mm
Manufacturer Item Number	NJ 214 ECJ

Number of Rows of Rollers	Single Row
Basic dynamic load rating C	137 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	137 kN
Fatigue load limit P_u	18 kN
Calculation factor k_r	0.15
Fatigue load limit - P_u	18 kN
Calculation factor - k_r	0.15
Basic static load rating C_0	137 kN
Basic static load rating - C_0	137 kN