



Bearing No. NJ 1034 ML

s	5.8 mm
d	170 mm
D	260 mm
B	42 mm
F	193 mm
s max.	5.8 mm
Size (mm)	260x170x42
Width (mm)	42
Mass bearing	8.18 kg
d_1	201 mm
D_1	226.9 mm
Limiting speed	4300 r/min
Bearing number	NJ 1034 ML
Reference speed	2800 r/min
Limiting value e	0.2
d_a min.	180 mm
Bore Diameter (mm)	260
D_a max.	250 mm
d_b min.	206 mm
r_a max.	2 mm
d_a max.	189 mm
Axial load factor Y	0.6
Outer Diameter (mm)	170
r_a - max.	2 mm
D_a - max.	250 mm
d_a - min.	180 mm
$r_{3,4}$ min.	2.1 mm
d_b - min.	206 mm
d_a - max.	189 mm
$r_{1,2}$ min.	2.1 mm

d_1 ?	201 mm
D_1 ?	226.9 mm
$r_{3,4}$ - min.	2.1 mm
$r_{1,2}$ - min.	2.1 mm
Basic dynamic load rating C	275 kN
Basic dynamic load rating - C	275 kN
Fatigue load limit P_u	41.5 kN
Calculation factor k_r	0.15
Calculation factor - k_r	0.15
Fatigue load limit - P_u	41.5 kN
Basic static load rating C_0	400 kN
Basic static load rating - C_0	400 kN