



Bearing No. S7022 CE/HCP4A

D	170 mm
d	110 mm
B	28 mm
a	32.9 mm
Ball - z	30
Size (mm)	170x110x28
Width (mm)	28
Mass bearing	2 kg
D ₂	152.2 mm
d ₂	129.2 mm
d ₁	132.38 mm
d ₂	129.2 mm
D ₂	152.2 mm
d ₁	132.38 mm
Bearing number	S7022 CE/HCP4A
Preload class B	165 N/micron
Preload class A	104 N/micron
Preload class C	226 N/micron
Number of balls z	30
Bore Diameter (mm)	170
d _a min.	118.8 mm
d _a max.	131.6 mm
d _b min.	118.8 mm
d _b max.	128.4 mm
D _a max.	161.2 mm
D _b max.	164.4 mm
r _a max.	2 mm
r _b max.	1 mm
Outer Diameter (mm)	110
r _{3,4} min.	1 mm

d_b - min.	118.8 mm
Calculation factor f	1.1
d_a - max.	131.6 mm
$r_{1,2}$ min.	2 mm
D_a - max.	161.2 mm
d_b - max.	128.4 mm
D_b - max.	164.4 mm
r_a - max.	2 mm
d_a - min.	118.8 mm
Ball - D_w	12.7 mm
r_b - max.	1 mm
$r_{3,4}$ - min.	1 mm
Calculation factor - f	1.1
$r_{1,2}$ - min.	2 mm
Basic dynamic load rating C	47.5 kN
Ball diameter D_w	12.7 mm
Basic dynamic load rating - C	47.5 kN
Preload class A G_A	250 N
Preload class B G_B	760 N
Preload class C G_C	1520 N
Preload class A - G_A	250 N
Preload class B - G_B	760 N
Preload class C - G_C	1520 N
Fatigue load limit P_u	1.6 kN
Calculation factor f_1	1
Calculation factor f_0	9.6
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1.01
Calculation factor f_{2B}	1.03
Calculation factor f_{2A}	1

Calculation factor - f	1
Calculation factor - f_0	9.6
Fatigue load limit - P_u	1.6 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.03
Calculation factor - f_{HC}	1.01
Limiting speed for grease lubrication	12700 r/min
Basic static load rating C_0	45 kN
Static axial stiffness, preload class B	165 N/ μ m
Static axial stiffness, preload class C	226 N/ μ m
Static axial stiffness, preload class A	104 N/ μ m
Attainable speed for grease lubrication	12700 r/min
Basic static load rating - C_0	45 kN