



Bearing No. 306890

| | |
|-----------------------------------|------------|
| D | 480 mm |
| d | 340 mm |
| B | 60 mm |
| Size (mm) | 480x340x60 |
| Width (mm) | 60 |
| Mass bearing | 36 kg |
| D ₁ | 432.8 mm |
| d ₁ | 387.1 mm |
| Limiting speed | 1600 r/min |
| Bearing number | 306890 |
| Reference speed | 2600 r/min |
| r _a max. | 3 mm |
| D _a max. | 465 mm |
| Bore Diameter (mm) | 480 |
| d _a min. | 355 mm |
| Outer Diameter (mm) | 340 |
| D _a - max. | 465 mm |
| r _a - max. | 3 mm |
| r _{1,2} min. | 4 mm |
| d _a - min. | 355 mm |
| d ₁ ? | 387.1 mm |
| D ₁ ? | 432.8 mm |
| r _{1,2} - min. | 4 mm |
| Basic dynamic load rating C | 291 kN |
| Basic dynamic load rating - C | 291 kN |
| Fatigue load limit P _u | 9 kN |
| Calculation factor k _r | 0.02 |
| Calculation factor f ₀ | 17 |
| | |

| | |
|-------------------------------------|--------|
| Calculation factor - f_0 | 17 |
| Calculation factor - k_r | 0.02 |
| Fatigue load limit - P_u | 9 kN |
| Basic static load rating C_0 | 430 kN |
| Basic static load rating - C_0 | 430 kN |