



Bearing No. 51212

C	71.5
r	1
d	60 mm
D	95 mm
T	26 mm
D1	62 mm
da	81
ra	1
B_	26
C0	169
d1	95 mm
D_	95
T_	26
Z_	17
DA_	12.7
SRE	6.85
D_a	74
D_1	62
SRI	6.85
KBRG	5111
SREN	0
Noun	Bearing
SRIX	0.05
SRIN	0
mass	0.673
SDM_	77.5
SREX	0.05
yobi	51212
r min.	1 mm
Banded	No

Weight	0,673 Kg
LangID	1
Bore 2	2.441 Inch 62 Millimeter
Height	1.024 Inch 26 Millimeter
UNSPSC	31171552
Bore 1	2.362 Inch 60 Millimeter
Oil rpm	3000
da min.	81 mm
GRS rpm	2000
ra max.	1 mm
Da max.	74 mm
hidYobi	51212
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	60x95x26
Inventory	0.0
Width (mm)	26
Prod_Type3	TB_SD_WFS
Weight / LBS	1.48371
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	51212
overall width:	26 mm
Keyword String	Ball Thrust
Thrust Bearing	Yes
bore diameter:	60 mm
Other Features	Single Row With Flat Seat
Rolling Element	Ball Bearing

Precision Class	Non-Precision
Manufacturer URL	http://www.nskamericas.com
Long Description	60MM Bore 1; 62MM Bore 2; 95MM Outside Diameter; 26MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	3.74 Inch 95 Millimeter
Weight / Kilogram	0.69
Manufacturer Name	NSK
outside diameter:	95 mm
Bore Diameter (mm)	60
Outer Diameter (mm)	95
thrust bearing type:	Single-Direction
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
manufacturer upc number:	029176062315
Manufacturer Item Number	51212
Single or Double Direction	Single Direction
(Grease) Lubrication Speed	2000 r/min
Basic static load rating (C0)	169 kN
Basic dynamic load rating (C)	71,5 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter