



Bearing No. S7009 ACD/HCP4A

D	75 mm
d	45 mm
B	16 mm
a	22.1 mm
Ball - z	17
Size (mm)	75x45x16
Width (mm)	16
Mass bearing	0.2 kg
D ₂	68.3 mm
d ₂	54.2 mm
d ₁	54.2 mm
d ₂	54.2 mm
D ₂	68.3 mm
d ₁	54.2 mm
Bearing number	S7009 ACD/HCP4A
Preload class B	192 N/micron
Preload class A	146 N/micron
Preload class D	343 N/micron
Preload class C	254 N/micron
Number of balls z	17
r _b max.	0.3 mm
r _a max.	1 mm
D _b max.	73 mm
D _a max.	70.4 mm
d _b max.	53.7 mm
d _b min.	49.6 mm
d _a max.	53.7 mm
Bore Diameter (mm)	75
d _a min.	49.6 mm
Outer Diameter (mm)	45

d _a - max.	53.7 mm
d _a - min.	49.6 mm
Calculation factor e	0.68
Calculation factor f	1.09
d _b - max.	53.7 mm
D _b - max.	73 mm
r _a - max.	1 mm
r _b - max.	0.3 mm
d _b - min.	49.6 mm
r _{3,4} min.	0.3 mm
r _{1,2} min.	1 mm
Ball - D _w	9.525 mm
D _a - max.	70.4 mm
r _{3,4} - min.	0.3 mm
r _{1,2} - min.	1 mm
Calculation factor - f	1.09
Calculation factor - e	0.68
Ball diameter D _w	9.525 mm
Basic dynamic load rating C	27.6 kN
Preload class A G _A	170 N
Basic dynamic load rating - C	27.6 kN
Preload class B G _B	340 N
Preload class C G _C	680 N
Preload class D G _D	1360 N
Preload class B - G _B	340 N
Preload class C - G _C	680 N
Preload class A - G _A	170 N
Preload class D - G _D	1360 N
Calculation factor f ₁	0.99
Fatigue load limit P _u	0.9 kN

Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1.02
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.9 kN
Calculation factor - Y_0	0.76
Calculation factor - f_1	0.99
Calculation factor - f_{HC}	1.02
Calculation factor - f_{2D}	1.08
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	20000 r/min
Basic static load rating C_0	21.6 kN
Static axial stiffness, preload class D	343 N/ μ m
Attainable speed for grease lubrication	20000 r/min
Static axial stiffness, preload class C	254 N/ μ m
Static axial stiffness, preload class B	192 N/ μ m
Static axial stiffness, preload class A	146 N/ μ m
Basic static load rating - C_0	21.6 kN

Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67