



Bearing No. S7010 ACB/P4A

D	80 mm
d	50 mm
B	16 mm
a	23.2 mm
Ball - z	27
Size (mm)	80x50x16
Width (mm)	16
Mass bearing	0.29 kg
D_2	70.7 mm
d_2	59.65 mm
d_1	61.44 mm
d_2	59.65 mm
D_2	70.7 mm
d_1	61.44 mm
Bearing number	S7010 ACB/P4A
Preload class A	87 N/micron
Preload class B	110 N/micron
Preload class C	165 N/micron
Number of balls z	27
r_b max.	0.6 mm
r_a max.	1 mm
D_b max.	76.8 mm
D_a max.	75.4 mm
d_b max.	59.1 mm
d_b min.	54.6 mm
d_a max.	60.8 mm
Bore Diameter (mm)	80
d_a min.	54.6 mm
Outer Diameter (mm)	50
d_a - max.	60.8 mm

d_a - min.	54.6 mm
Calculation factor e	0.68
Calculation factor f	1.06
d_b - max.	59.1 mm
D_a - max.	75.4 mm
r_a - max.	1 mm
r_b - max.	0.6 mm
d_b - min.	54.6 mm
$r_{3,4}$ min.	0.6 mm
$r_{1,2}$ min.	1 mm
Ball - D_w	5.556 mm
D_b - max.	76.8 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - f	1.06
Calculation factor - e	0.68
$r_{1,2}$ - min.	1 mm
Basic dynamic load rating C	12.5 kN
Ball diameter D_w	5.556 mm
Preload class A G_A	147 N
Basic dynamic load rating - C	9.4 kN
Preload class C G_C	330 N
Preload class B G_B	110 N
Preload class B - G_B	110 N
Preload class A - G_A	147 N
Preload class C - G_C	330 N
Calculation factor f_1	0.99
Fatigue load limit P_u	0.31 kN
Calculation factor f_{HC}	1
Calculation factor f_{2C}	1.04
Calculation factor f_{2B}	1.01

Calculation factor f_{2A}	1
Calculation factor - X_2	0.67
Calculation factor - Y_0	0.76
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.31 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.01
Calculation factor - f_{2C}	1.04
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	22000 r/min
Basic static load rating C_0	12.2 kN
Static axial stiffness, preload class C	165 N/ μ m
Static axial stiffness, preload class B	110 N/ μ m
Attainable speed for grease lubrication	22000 r/min
Static axial stiffness, preload class A	87 N/ μ m
Basic static load rating - C_0	7.4 kN
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-	1.41

to-back, face-to-face) Y_2	
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67