



Bearing No. S7010 CE/HCP4A

D	80 mm
d	50 mm
B	16 mm
a	16.8 mm
Ball - z	21
Size (mm)	80x50x16
Width (mm)	16
Mass bearing	0.23 kg
D ₂	72.9 mm
d ₂	57.9 mm
d ₁	60.25 mm
d ₂	57.9 mm
D ₂	72.9 mm
d ₁	60.25 mm
Bearing number	S7010 CE/HCP4A
Preload class B	72 N/micron
Preload class A	46 N/micron
Preload class C	98 N/micron
Number of balls z	21
Bore Diameter (mm)	80
d _a min.	54.6 mm
d _a max.	59.7 mm
d _b min.	54.6 mm
d _b max.	57.3 mm
D _a max.	75.4 mm
D _b max.	75.8 mm
r _a max.	1 mm
r _b max.	0.6 mm
Outer Diameter (mm)	50
r _{3,4} min.	0.6 mm

d_b - min.	54.6 mm
Calculation factor f	1.08
d_a - max.	59.7 mm
$r_{1,2}$ min.	1 mm
D_a - max.	75.4 mm
d_b - max.	57.3 mm
D_b - max.	75.8 mm
r_a - max.	1 mm
d_a - min.	54.6 mm
Ball - D_w	7.938 mm
r_b - max.	0.6 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - f	1.08
$r_{1,2}$ - min.	1 mm
Basic dynamic load rating C	15.6 kN
Ball diameter D_w	7.938 mm
Basic dynamic load rating - C	15.6 kN
Preload class A G_A	85 N
Preload class B G_B	250 N
Preload class C G_C	500 N
Preload class A - G_A	85 N
Preload class B - G_B	250 N
Preload class C - G_C	500 N
Fatigue load limit P_u	0.45 kN
Calculation factor f_1	1
Calculation factor f_0	8.2
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1.01
Calculation factor f_{2B}	1.03
Calculation factor f_{2A}	1

Calculation factor - f	1
Calculation factor - f_0	8.2
Fatigue load limit - P_u	0.45 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.03
Calculation factor - f_{HC}	1.01
Limiting speed for grease lubrication	30000 r/min
Basic static load rating C_0	10.6 kN
Static axial stiffness, preload class B	72 N/ μ m
Static axial stiffness, preload class C	98 N/ μ m
Static axial stiffness, preload class A	46 N/ μ m
Attainable speed for grease lubrication	30000 r/min
Basic static load rating - C_0	10.6 kN