




Bearing No. S7005 CE/P4A

D	47 mm
d	25 mm
B	12 mm
a	10.8 mm
Ball - z	14
Size (mm)	47x25x12
Width (mm)	12
Mass bearing	0.077 kg
D ₂	41.5 mm
d ₂	29.8 mm
d ₁	31.6 mm
d ₂	29.8 mm
D ₂	41.5 mm
d ₁	31.6 mm
Bearing number	S7005 CE/P4A
Preload class B	37 N/micron
Preload class A	24 N/micron
Preload class C	50 N/micron
Number of balls z	14
Bore Diameter (mm)	47
d _a min.	28.2 mm
d _a max.	31.2 mm
d _b min.	28.2 mm
d _b max.	29.4 mm
D _a max.	43.8 mm
D _b max.	44.6 mm
r _a max.	0.6 mm
r _b max.	0.3 mm
Outer Diameter (mm)	25
r _{3,4} min.	0.3 mm

d_b - min.	28.2 mm
Calculation factor f	1.05
d_a - max.	31.2 mm
$r_{1,2}$ min.	0.6 mm
D_a - max.	43.8 mm
d_b - max.	29.4 mm
D_b - max.	44.6 mm
r_a - max.	0.6 mm
d_a - min.	28.2 mm
Ball - D_w	6.35 mm
r_b - max.	0.3 mm
$r_{3,4}$ - min.	0.3 mm
Calculation factor - f	1.05
$r_{1,2}$ - min.	0.6 mm
Basic dynamic load rating C	8.32 kN
Ball diameter D_w	6.35 mm
Basic dynamic load rating - C	8.3 kN
Preload class A G_A	45 N
Preload class B G_B	130 N
Preload class C G_C	260 N
Preload class A - G_A	45 N
Preload class B - G_B	130 N
Preload class C - G_C	260 N
Fatigue load limit P_u	0.173 kN
Calculation factor f_1	1
Calculation factor f_0	7.5
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1
Calculation factor f_{2B}	1.03
Calculation factor f_{2A}	1

Calculation factor - f	1
Calculation factor - f_0	7.5
Fatigue load limit - P_u	0.173 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.03
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	46000 r/min
Basic static load rating C_0	4.15 kN
Static axial stiffness, preload class B	37 N/ μ m
Static axial stiffness, preload class C	50 N/ μ m
Static axial stiffness, preload class A	24 N/ μ m
Attainable speed for grease lubrication	46000 r/min
Basic static load rating - C_0	4.2 kN