



Bearing No. S7003 ACE/HCP4A

D	35 mm
d	17 mm
B	10 mm
a	11.2 mm
Ball - z	12
Size (mm)	35x17x10
Width (mm)	10
Mass bearing	0.032 kg
D ₂	31.2 mm
d ₂	21.1 mm
d ₁	22.7 mm
d ₂	21.1 mm
D ₂	31.2 mm
d ₁	22.7 mm
Bearing number	S7003 ACE/HCP4A
Preload class A	51 N/micron
Preload class B	76 N/micron
Preload class C	99 N/micron
Number of balls z	12
r _b max.	0.15 mm
r _a max.	0.3 mm
D _b max.	33.6 mm
D _a max.	33 mm
d _b max.	20.7 mm
d _b min.	19 mm
d _a max.	22.3 mm
Bore Diameter (mm)	35
d _a min.	19 mm
Outer Diameter (mm)	17
d _a - max.	22.3 mm

d _a - min.	19 mm
Calculation factor e	0.68
Calculation factor f	1.04
d _b - max.	20.7 mm
D _a - max.	33 mm
r _a - max.	0.3 mm
r _b - max.	0.15 mm
d _b - min.	19 mm
r _{3,4} min.	0.15 mm
r _{1,2} min.	0.3 mm
Ball - D _w	5.556 mm
D _b - max.	33.6 mm
r _{3,4} - min.	0.15 mm
Calculation factor - f	1.04
Calculation factor - e	0.68
r _{1,2} - min.	0.3 mm
Basic dynamic load rating C	5.59 kN
Ball diameter D _w	5.556 mm
Preload class A G _A	50 N
Basic dynamic load rating - C	5.6 kN
Preload class C G _C	300 N
Preload class B G _B	150 N
Preload class B - G _B	150 N
Preload class A - G _A	50 N
Preload class C - G _C	300 N
Calculation factor f ₁	0.99
Fatigue load limit P _u	0.104 kN
Calculation factor f _{HC}	1.01
Calculation factor f _{2C}	1.06
Calculation factor f _{2B}	1.03

Calculation factor f_{2A}	1
Calculation factor - X_2	0.67
Calculation factor - Y_0	0.76
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.104 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.03
Calculation factor - f_{2C}	1.06
Calculation factor - f_{HC}	1.01
Limiting speed for grease lubrication	68000 r/min
Basic static load rating C_0	2.45 kN
Static axial stiffness, preload class C	99 N/ μm
Static axial stiffness, preload class B	76 N/ μm
Attainable speed for grease lubrication	68000 r/min
Static axial stiffness, preload class A	51 N/ μm
Basic static load rating - C_0	2.4 kN
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-	1.41

to-back, face-to-face) Y_2	
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67