




Bearing No. S7001 ACE/HCP4A

D	28 mm
d	12 mm
B	8 mm
a	8.8 mm
Ball - z	12
Size (mm)	28x12x8
Width (mm)	8
Mass bearing	0.019 kg
D ₂	24.35 mm
d ₂	16.5 mm
d ₁	17.5 mm
d ₂	16.5 mm
D ₂	24.35 mm
d ₁	17.5 mm
Bearing number	S7001 ACE/HCP4A
Preload class A	37 N/micron
Preload class B	56 N/micron
Preload class C	73 N/micron
Number of balls z	12
r _b max.	0.15 mm
r _a max.	0.3 mm
D _b max.	26.6 mm
D _a max.	26 mm
d _b max.	16.1 mm
d _b min.	14 mm
d _a max.	17.1 mm
Bore Diameter (mm)	28
d _a min.	14 mm
Outer Diameter (mm)	12
d _a - max.	17.1 mm

d_a - min.	14 mm
Calculation factor e	0.68
Calculation factor f	1.02
d_b - max.	16.1 mm
D_a - max.	26 mm
r_a - max.	0.3 mm
r_b - max.	0.15 mm
d_b - min.	14 mm
$r_{3,4}$ min.	0.15 mm
$r_{1,2}$ min.	0.3 mm
Ball - D_w	3.969 mm
D_b - max.	26.6 mm
$r_{3,4}$ - min.	0.15 mm
Calculation factor - f	1.02
Calculation factor - e	0.68
$r_{1,2}$ - min.	0.3 mm
Basic dynamic load rating C	3.07 kN
Ball diameter D_w	3.969 mm
Preload class A G_A	28 N
Basic dynamic load rating - C	3.1 kN
Preload class C G_C	170 N
Preload class B G_B	85 N
Preload class B - G_B	85 N
Preload class A - G_A	28 N
Preload class C - G_C	170 N
Calculation factor f_1	0.99
Fatigue load limit P_u	0.054 kN
Calculation factor f_{HC}	1.01
Calculation factor f_{2C}	1.06
Calculation factor f_{2B}	1.03

Calculation factor f_{2A}	1
Calculation factor - X_2	0.67
Calculation factor - Y_0	0.76
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.054 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.03
Calculation factor - f_{2C}	1.06
Calculation factor - f_{HC}	1.01
Limiting speed for grease lubrication	88000 r/min
Basic static load rating C_0	1.27 kN
Static axial stiffness, preload class C	73 N/ μ m
Static axial stiffness, preload class B	56 N/ μ m
Attainable speed for grease lubrication	88000 r/min
Static axial stiffness, preload class A	37 N/ μ m
Basic static load rating - C_0	1.3 kN
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-	1.41



to-back, face-to-face) Y_2	
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67