



Bearing No. S7001 CD/HCP4A

D	28 mm
d	12 mm
B	8 mm
a	6.7 mm
Ball - z	10
Size (mm)	28x12x8
Width (mm)	8
Mass bearing	0.018 kg
D ₂	25.5 mm
d ₂	17.1 mm
d ₁	17.1 mm
d ₂	17.1 mm
D ₂	25.5 mm
d ₁	17.1 mm
Bearing number	S7001 CD/HCP4A
Preload class A	15 N/micron
Preload class B	20 N/micron
Preload class D	38 N/micron
Preload class C	27 N/micron
Number of balls z	10
r _b max.	0.2 mm
r _a max.	0.3 mm
D _b max.	26.6 mm
D _a max.	26 mm
d _b max.	16.7 mm
d _a max.	16.7 mm
d _a min.	14 mm
Bore Diameter (mm)	28
d _b min.	14 mm
Outer Diameter (mm)	12

$r_{3,4}$ min.	0.2 mm
d_b - min.	14 mm
Calculation factor f	1.03
d_a - max.	16.7 mm
$r_{1,2}$ min.	0.3 mm
d_a - min.	14 mm
d_b - max.	16.7 mm
D_a - max.	26 mm
D_b - max.	26.6 mm
r_a - max.	0.3 mm
r_b - max.	0.2 mm
Ball - D_w	4.762 mm
$r_{3,4}$ - min.	0.2 mm
Calculation factor - f	1.03
$r_{1,2}$ - min.	0.3 mm
Ball diameter D_w	4.762 mm
Basic dynamic load rating C	4.49 kN
Preload class A G_A	15 N
Basic dynamic load rating - C	4.5 kN
Preload class C G_C	60 N
Preload class D G_D	120 N
Preload class B G_B	30 N
Preload class C - G_C	60 N
Preload class D - G_D	120 N
Preload class B - G_B	30 N
Preload class A - G_A	15 N
Calculation factor f_1	1
Fatigue load limit P_u	0.08 kN
Calculation factor f_0	8.7
Calculation factor f_{2D}	1.09

Calculation factor f_{HC}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2B}	1.02
Calculation factor f_{2A}	1
Calculation factor - f	1
Calculation factor - f_0	8.7
Fatigue load limit - P_u	0.08 kN
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2D}	1.09
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2A}	1
Calculation factor - f_{HC}	1.02
Limiting speed for grease lubrication	80000 r/min
Basic static load rating C_0	1.9 kN
Static axial stiffness, preload class A	15 N/ μ m
Static axial stiffness, preload class B	20 N/ μ m
Static axial stiffness, preload class C	27 N/ μ m
Static axial stiffness, preload class D	38 N/ μ m
Attainable speed for grease lubrication	80000 r/min
Basic static load rating - C_0	1.9 kN