



Bearing No. 22319UAVS2

D	200,000 mm
d	95,000 mm
H	67,000 mm
Noun	Bearing
Bore	3.74 Inch 95 Millimeter
Width	2.638 Inch 67 Millimeter
UNSPSC	31171510
series:	223
Category	Spherical Roller Bearing
Enclosure	Open
Inventory	0.0
Size (mm)	95x200x67
cage type:	Machined
Width (mm)	67,000
bore type:	Straight
Weight / LBS	22.984
maximum rpm:	2000 rpm
Bore Profile	Straight
closure type:	Open
Cage Material	Bronze
Inch - Metric	Metric
Product Group	B04311
Keyword String	Spherical
fillet radius:	3 mm
overall width:	67 mm
cage material:	Brass
bore diameter:	95 mm
Bearing number	22319UAVS2
Relubricatable	Yes

Withdrawal Nut	Not Applicable
Rolling Element	Spherical Roller Bearing
Mounting Method	Shaft Mount
finish/coating:	Uncoated
outer ring type:	Not Split
Long Description	95MM Straight Bore; 200MM Outside Diameter; 67MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Outside Diameter	7.874 Inch 200 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	10.44
outside diameter:	200 mm
Withdrawal Sleeve	Not Applicable
bearing material:	Through Hardened Steel
inner ring width:	67 mm
outer ring width:	67 mm
Manufacturer Name	NTN
Bore Diameter (mm)	95,000
Internal Clearance	C0-Medium
internal clearance:	Upper 2/3 of C4 range
Outer Diameter (mm)	200,000
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Minimum Buy Quantity	N/A
static load capacity:	465000 N
Harmonized Tariff Code	84823080
lubrication hole type:	Lubrication Groove &

	Hole
dynamic load capacity:	490000 N
Number of Rows of Rollers	Double Row
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C