



Bearing No. 22322UAVS2

D	240,000 mm
d	110,000 mm
H	80,000 mm
Noun	Bearing
Bore	4.331 Inch 110 Millimeter
Width	3.15 Inch 80 Millimeter
UNSPSC	31171510
series:	223
Category	Spherical Roller Bearing
Enclosure	Open
Inventory	0.0
Size (mm)	110x240x80
cage type:	Machined
Width (mm)	80,000
bore type:	Straight
Weight / LBS	40.045
maximum rpm:	1700 rpm
Bore Profile	Straight
closure type:	Open
Cage Material	Bronze
Inch - Metric	Metric
Product Group	B04311
Keyword String	Spherical
fillet radius:	3 mm
overall width:	80 mm
cage material:	Brass
bore diameter:	110 mm
Bearing number	22322UAVS2
Relubricatable	Yes

Withdrawal Nut	Not Applicable
Rolling Element	Spherical Roller Bearing
Mounting Method	Shaft Mount
finish/coating:	Uncoated
outer ring type:	Not Split
Long Description	110MM Straight Bore; 240MM Outside Diameter; 80MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Outside Diameter	9.449 Inch 240 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	18.18
outside diameter:	240 mm
Withdrawal Sleeve	Not Applicable
bearing material:	Through Hardened Steel
inner ring width:	80 mm
outer ring width:	80 mm
Manufacturer Name	NTN
Bore Diameter (mm)	110,000
Internal Clearance	C0-Medium
internal clearance:	Upper 2/3 of C4 range
Outer Diameter (mm)	240,000
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Minimum Buy Quantity	N/A
static load capacity:	710000 N
Harmonized Tariff Code	84823080
lubrication hole type:	Lubrication Groove &

	Hole
dynamic load capacity:	730000 N
Number of Rows of Rollers	Double Row
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C