



Bearing No. LM67048/LM67010

|      |           |
|------|-----------|
| e    | 0.41      |
| D    | 59,131 mm |
| C    | 11,811 mm |
| B    | 16,764 mm |
| T    | 15,875 mm |
| a    | 12,6 mm   |
| d    | 31.75 mm  |
| da   | 42,5 mm   |
| D_   | 59.131    |
| B_   | 16.764    |
| Y1   | 1.5       |
| Db   | 56 mm     |
| db   | 36 mm     |
| Da   | 52 mm     |
| Z_   | 19        |
| C0   | 41.5      |
| C_   | 11.811    |
| Y0   | 0.8       |
| D_a  | 52        |
| D_b  | 56        |
| SLR  | 10.7      |
| RAr  | 101.566   |
| DE_  | 51.19     |
| DI_  | 38.971    |
| CUP  | 0.062     |
| DA_  | 6.159     |
| DA1  | 6.498     |
| DA2  | 5.817     |
| SDM_ | 45.031    |
| CONE | 0.127     |
|      |           |

|                         |                     |
|-------------------------|---------------------|
| KBRG                    | 3161                |
| yobi                    | LM67048/LM67010     |
| ALP22                   | 44                  |
| BETA_                   | 1                   |
| BET23                   | 0                   |
| BET22                   | 40                  |
| BET21                   | 3                   |
| ALP21                   | 30                  |
| ALP23                   | 0                   |
| LangID                  | 1                   |
| ALPHA_                  | 15.367              |
| Weight                  | 0,189 Kg            |
| Oil rpm                 | 8500                |
| hidYobi                 | LM67048/LM67010     |
| inner r                 | SPEC                |
| ra max.                 | 3,5 mm              |
| outer r                 | 1.3                 |
| GRS rpm                 | 6300                |
| r1 min.                 | 1,3 mm              |
| hidTable                | ecat_NSTPRI         |
| inner ra                | 3.5                 |
| outer rb                | 1.3                 |
| ra1 max.                | 1,3 mm              |
| Size (mm)               | 31.75x59.131x15.875 |
| SHOG_yobi               | LM67048R/LM67010R   |
| Prod_Type3              | TRBSR_ID_A          |
| Width (mm)              | 15,875              |
| Bearing number          | LM67048/LM67010     |
| Bore Diameter (mm)      | 31.75               |
| Outer Diameter (mm)     | 59,131              |
| Calculation factor (e)  | 0,41                |
| Calculation factor (Y0) | 0,8                 |
|                         |                     |

|                               |            |
|-------------------------------|------------|
| (Oil) Lubrication Speed       | 8500 r/min |
| (Grease) Lubrication Speed    | 6300 r/min |
| Basic dynamic load rating (C) | 34,5 kN    |
| Basic static load rating (C0) | 41,5 kN    |