



Bearing No. 22268R

| | |
|------------------------|-------------|
| D | 620 mm |
| d | 340 mm |
| B | 165 mm |
| C | 165 mm |
| e | 0.28 |
| Cu | 551 |
| Y1 | 2.43 |
| Y0 | 2.37 |
| Y2 | 3.61 |
| Cr | 4430 |
| C0r | 5430 |
| r(min) | 6 |
| Weight | 221 Kg |
| r min. | 6 mm |
| ra max. | 5 mm |
| Da max. | 592 mm |
| ra(max) | 5 |
| Da(max) | 592 |
| da(min) | 368 |
| da min. | 368 mm |
| Oil lub. | 590 |
| Size (mm) | 340x620x165 |
| Width (mm) | 165 |
| Grease lub. | 440 |
| Bearing No. | 22268R |
| Bearing number | 22268R |
| (Refer.)Mass(kg) | 221 |
| Bore Diameter (mm) | 340 |
| Outer Diameter (mm) | 620 |
| Calculation factor (e) | 0,28 |

| | |
|-------------------------------|-----------|
| Calculation factor (Y1) | 2,43 |
| Calculation factor (Y0) | 2,37 |
| (Oil) Lubrication Speed | 590 r/min |
| (Grease) Lubrication Speed | 440 r/min |
| Basic static load rating (C0) | 5430 kN |
| Basic dynamic load rating (C) | 3550 kN |