



Bearing No. LM67043/LM67010

e	0.41
D	59,131 mm
C	11,811 mm
B	16,764 mm
T	15,875 mm
a	12,6 mm
d	28,575 mm
da	40 mm
D_	59.131
B_	16.764
Y1	1.5
Db	56 mm
db	33,5 mm
Da	52 mm
Z_	19
C0	41.5
C_	11.811
Y0	0.8
D_a	52
D_b	56
SLR	10.7
RAr	101.566
DE_	51.19
DI_	38.971
CUP	0.062
DA_	6.159
DA1	6.498
DA2	5.817
SDM_	45.031
CONE	0.147

KBRG	3161
yobi	LM67043/LM67010
ALP22	44
BETA_	1
BET23	0
BET22	40
BET21	3
ALP21	30
ALP23	0
LangID	1
ALPHA_	15.367
Weight	0,209 Kg
Oil rpm	8500
hidYobi	LM67043/LM67010
inner r	SPEC
ra max.	3,5 mm
outer r	1.3
GRS rpm	6300
r1 min.	1,3 mm
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	28.575x59.131x15.875
SHOG_yobi	LM67043R/LM67010R
Prod_Type3	TRBSR_ID_A
Width (mm)	15,875
Bearing number	LM67043/LM67010
Bore Diameter (mm)	28,575
Outer Diameter (mm)	59,131
Calculation factor (e)	0,41
Calculation factor (Y0)	0,8

(Oil) Lubrication Speed	8500 r/min
(Grease) Lubrication Speed	6300 r/min
Basic dynamic load rating (C)	34,5 kN
Basic static load rating (C0)	41,5 kN