



Bearing No. 21075/21212

e	0.59
d	19.05 mm
D	53,975 mm
T	22,225 mm
B	21,839 mm
C	15,875 mm
a	16,3 mm
Da	43 mm
B_	21.839
Db	50 mm
da	31,5 mm
Y0	0.56
db	26 mm
C0	39.5
D_	53.975
Z_	11
C_	15.875
Y1	1
DE_	43.483
SLR	14.6
D_a	43
DI_	27.593
DA1	9.268
DA2	7.251
CUP	0.097
DA_	8.272
D_b	50
RAr	66.446
SDM_	35.571
KBRG	3161

yobi	21075/21212
CONE	0.156
ALP21	43
ALP22	0
ALP23	0
BETA_	4
BET21	8
BET23	0
BET22	0
r min.	1,5 mm
LangID	1
Weight	0,253 Kg
ALPHA_	21.5
r1 min.	2,3 mm
ra max.	1,5 mm
Oil rpm	10000
outer r	2.3
hidYobi	21075/21212
GRS rpm	7500
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	2.3
ra1 max.	2,3 mm
Size (mm)	19.05x53.975x22.225
SHOG_yobi	21075R/21212R
Prod_Type3	TRBSR_ID_A
Width (mm)	22,225
Bearing number	21075/21212
Bore Diameter (mm)	19.05
Outer Diameter (mm)	53,975
Calculation factor (e)	0,59

(Oil) Lubrication Speed	10000 r/min
Calculation factor (Y0)	0,56
(Grease) Lubrication Speed	7500 r/min
Basic static load rating (C0)	39,5 kN
Basic dynamic load rating (C)	40,5 kN