



Bearing No. 22168/22325

e	0.43
d	42,862 mm
D	82,55 mm
T	19,842 mm
B	19,837 mm
C	15,08 mm
a	17,6 mm
Da	73 mm
B_	19.837
Db	76 mm
da	52 mm
Y0	0.77
db	48,5 mm
C0	69
D_	82.55
Z_	18
C_	15.08
Y1	1.4
DE_	69.849
SLR	13
D_a	73
DI_	52.665
DA1	9.289
DA2	8.388
CUP	0.176
DA_	8.842
D_b	76
RAr	133.096
SDM_	61.324
KBRG	3161

yobi	22168/22325
CONE	0.283
ALP21	32
ALP22	2
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	0
r min.	2,3 mm
LangID	1
Weight	0,459 Kg
ALPHA_	16.017
r1 min.	1,5 mm
ra max.	2,3 mm
Oil rpm	6300
outer r	1.5
hidYobi	22168/22325
GRS rpm	4500
inner r	2.3
hidTable	ecat_NSTPRI
inner ra	2.3
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	42.862x82.55x19.842
SHOG_yobi	22168R/22325R
Prod_Type3	TRBSR_ID_A
Width (mm)	19,842
Bearing number	22168/22325
Bore Diameter (mm)	42,862
Outer Diameter (mm)	82,55
Calculation factor (e)	0,43

(Oil) Lubrication Speed	6300 r/min
Calculation factor (Y0)	0,77
(Grease) Lubrication Speed	4500 r/min
Basic static load rating (C0)	69 kN
Basic dynamic load rating (C)	58,5 kN