



Bearing No. 230/600 CAK/W33 + AOHX 30/600

D	870 mm
B	200 mm
b	22.3 mm
K	12 mm
G	Tr 630x6
Size (mm)	870x570x200
Width (mm)	200
d ₂	685 mm
G ₁	630 mm
G ₁	45 mm
B ₁	245 mm
d ₁	570 mm
D ₁	789 mm
B ₁	245 mm
d ₁	570 mm
Bearing number	230/600 CAK/W33 + AOHX 30/600
Limiting speed	700 r/min
Reference speed	400 r/min
D _a max.	847 mm
r _a max.	5 mm
d _a min.	613 mm
Bore Diameter (mm)	870
Outer Diameter (mm)	570
r _a - max.	5 mm
Calculation factor e	0.22
D _a - max.	847 mm
d _a - min.	613 mm
r _{1,2} min.	6 mm
	259 mm

B ² ?	
------------------	--

D_1 ?	789 mm
d_2 ?	685 mm
Mass bearing + sleeve	480 kg
$r_{1,2}$ - min.	6 mm
Calculation factor - e	0.22
Basic dynamic load rating C	6252 kN
Basic dynamic load rating - C	6252 kN
Fatigue load limit P_u	735 kN
Calculation factor Y_1	3
Calculation factor Y_2	4.6
Calculation factor Y_0	2.8
Calculation factor - Y_2	4.6
Calculation factor - Y_1	3
Fatigue load limit - P_u	735 kN
Basic static load rating C_0	11400 kN
Basic static load rating - C_0	11400 kN