



Bearing No. 23038 CCK/W33 + AH 3038 G

D	290 mm
B	75 mm
b	13.9 mm
K	7.5 mm
G	M 200x3
Size (mm)	290x180x75
Width (mm)	75
d ₂	216 mm
G ₁	200 mm
G ₁	18 mm
B ₁	96 mm
d ₁	180 mm
D ₁	261 mm
B ₁	96 mm
d ₁	180 mm
Bearing number	23038 CCK/W33 + AH 3038 G
Limiting speed	2400 r/min
Reference speed	1900 r/min
D _a max.	279 mm
r _a max.	2 mm
d _a min.	197 mm
Bore Diameter (mm)	290
Outer Diameter (mm)	180
r _a - max.	2 mm
Calculation factor e	0.23
D _a - max.	279 mm
d _a - min.	197 mm
r _{1,2} min.	2.1 mm
	102 mm

B ² ?	
------------------	--

D_1 ?	261 mm
d_2 ?	216 mm
Mass bearing + sleeve	21 kg
$r_{1,2}$ - min.	2.1 mm
Calculation factor - e	0.23
Basic dynamic load rating C	916 kN
Basic dynamic load rating - C	916 kN
Fatigue load limit P_u	122 kN
Calculation factor Y_1	2.9
Calculation factor Y_2	4.4
Calculation factor Y_0	2.8
Calculation factor - Y_2	4.4
Calculation factor - Y_1	2.9
Fatigue load limit - P_u	122 kN
Basic static load rating C_0	1340 kN
Basic static load rating - C_0	1340 kN