



Bearing No. 23044 CCK/W33 + AOH 3044 G

D	340 mm
B	90 mm
b	13.9 mm
K	7.5 mm
G	Tr 230x4
Size (mm)	340x200x90
Width (mm)	90
d ₂	250 mm
G ₁	230 mm
G ₁	20 mm
B ₁	111 mm
d ₁	200 mm
D ₁	306 mm
B ₁	111 mm
d ₁	200 mm
Bearing number	23044 CCK/W33 + AOH 3044 G
Limiting speed	2000 r/min
Reference speed	1600 r/min
D _a max.	327 mm
r _a max.	2.5 mm
d _a min.	227 mm
Bore Diameter (mm)	340
Outer Diameter (mm)	200
r _a - max.	2.5 mm
Calculation factor e	0.24
D _a - max.	327 mm
d _a - min.	227 mm
r _{1,2} min.	3 mm
	117 mm

B² ?

D_1 ?	306 mm
d_2 ?	250 mm
Mass bearing + sleeve	36.5 kg
$r_{1,2}$ - min.	3 mm
Calculation factor - e	0.24
Basic dynamic load rating C	1261 kN
Basic dynamic load rating - C	1261 kN
Fatigue load limit P_u	163 kN
Calculation factor Y_1	2.8
Calculation factor Y_2	4.2
Calculation factor Y_0	2.8
Calculation factor - Y_2	4.2
Calculation factor - Y_1	2.8
Fatigue load limit - P_u	163 kN
Basic static load rating C_0	1860 kN
Basic static load rating - C_0	1860 kN