



Bearing No. 23064 CCK/W33 + AOH 3064 G

D	480 mm
B	121 mm
b	16.7 mm
K	9 mm
G	Tr 340x5
Size (mm)	480x300x121
Width (mm)	121
d ₂	360 mm
G ₁	340 mm
G ₁	27 mm
B ₁	149 mm
d ₁	300 mm
D ₁	434 mm
B ₁	149 mm
d ₁	300 mm
Bearing number	23064 CCK/W33 + AOH 3064 G
Limiting speed	1400 r/min
Reference speed	1100 r/min
D _a max.	465 mm
r _a max.	3 mm
d _a min.	327 mm
Bore Diameter (mm)	480
Outer Diameter (mm)	300
r _a - max.	3 mm
Calculation factor e	0.23
D _a - max.	465 mm
d _a - min.	327 mm
r _{1,2} min.	4 mm
	157 mm

B² ?

D_1 ?	434 mm
d_2 ?	360 mm
Mass bearing + sleeve	89 kg
$r_{1,2}$ - min.	4 mm
Calculation factor - e	0.23
Basic dynamic load rating C	2348 kN
Basic dynamic load rating - C	2348 kN
Fatigue load limit P_u	285 kN
Calculation factor Y_1	2.9
Calculation factor Y_2	4.4
Calculation factor Y_0	2.8
Calculation factor - Y_2	4.4
Calculation factor - Y_1	2.9
Fatigue load limit - P_u	285 kN
Basic static load rating C_0	3800 kN
Basic static load rating - C_0	3800 kN