



Bearing No. 23072 CCK/W33 + AOH 3072 G

D	540 mm
B	134 mm
b	22.3 mm
K	12 mm
G	Tr 380x5
Size (mm)	540x340x134
Width (mm)	134
d ₂	404 mm
G ₁	380 mm
G ₁	30 mm
B ₁	167 mm
d ₁	340 mm
D ₁	483 mm
B ₁	167 mm
d ₁	340 mm
Bearing number	23072 CCK/W33 + AOH 3072 G
Limiting speed	1200 r/min
Reference speed	950 r/min
r _a max.	4 mm
D _a max.	522 mm
d _a min.	369 mm
Bore Diameter (mm)	540
Outer Diameter (mm)	340
D _a - max.	522 mm
Calculation factor e	0.23
d _a - min.	369 mm
r _{1,2} min.	5 mm
r _a - max.	4 mm
	483 mm

D¹ ?

--	--

B ₂ ?	176 mm
d ₂ ?	404 mm
Mass bearing + sleeve	125 kg
r _{1,2} - min.	5 mm
Calculation factor - e	0.23
Basic dynamic load rating C	2850 kN
Basic dynamic load rating - C	2850 kN
Fatigue load limit P _u	345 kN
Calculation factor Y ₁	2.9
Calculation factor Y ₂	4.4
Calculation factor Y ₀	2.8
Calculation factor - Y ₂	4.4
Calculation factor - Y ₁	2.9
Fatigue load limit - P _u	345 kN
Basic static load rating C ₀	4800 kN
Basic static load rating - C ₀	4800 kN
BS2_003.BDW30.description - B ₂	176 mm