



Bearing No. 23084 CAK/W33 + AOH 3084 G

D	620 mm
B	150 mm
b	22.3 mm
K	12 mm
G	Tr 440x5
Size (mm)	620x400x150
Width (mm)	150
d <sub>2</sub>	487 mm
G <sub>1</sub>	440 mm
G <sub>1</sub>	34 mm
B <sub>1</sub>	186 mm
d <sub>1</sub>	400 mm
D <sub>1</sub>	563 mm
B <sub>1</sub>	186 mm
d <sub>1</sub>	400 mm
Bearing number	23084 CAK/W33 + AOH 3084 G
Limiting speed	1100 r/min
Reference speed	600 r/min
D <sub>a</sub> max.	602 mm
r <sub>a</sub> max.	4 mm
d <sub>a</sub> min.	429 mm
Bore Diameter (mm)	620
Outer Diameter (mm)	400
r <sub>a</sub> - max.	4 mm
Calculation factor e	0.22
D <sub>a</sub> - max.	602 mm
d <sub>a</sub> - min.	429 mm
r <sub>1,2</sub> min.	5 mm
	196 mm

B<sup>2</sup> ?

$D_1$ ?	563 mm
$d_2$ ?	487 mm
Mass bearing + sleeve	175 kg
$r_{1,2}$ - min.	5 mm
Calculation factor - e	0.22
Basic dynamic load rating C	3541 kN
Basic dynamic load rating - C	3541 kN
Fatigue load limit $P_u$	415 kN
Calculation factor $Y_1$	3
Calculation factor $Y_2$	4.6
Calculation factor $Y_0$	2.8
Calculation factor - $Y_2$	4.6
Calculation factor - $Y_1$	3
Fatigue load limit - $P_u$	415 kN
Basic static load rating $C_0$	6000 kN
Basic static load rating - $C_0$	6000 kN