



Bearing No. 23100/23256

e	0.73
d	25,4 mm
D	65,088 mm
T	22,225 mm
B	21,463 mm
C	15,875 mm
a	20 mm
Da	53 mm
B_	21.463
Db	61 mm
da	39 mm
Y0	0.45
db	34,5 mm
C0	47.5
D_	65.088
Z_	13
C_	15.875
Y1	0.82
DE_	52.459
SLR	14.6
D_a	53
DI_	36.469
DA1	9.268
DA2	7.251
CUP	0.142
DA_	8.272
D_b	61
RAr	66.446
SDM_	44.313
KBRG	3161

yobi	23100/23256
CONE	0.214
ALP21	52
ALP22	0
ALP23	0
BETA_	4
BET21	8
BET23	0
BET22	0
r min.	1,5 mm
LangID	1
Weight	0,356 Kg
ALPHA_	26
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	8000
outer r	1.5
hidYobi	23100/23256
GRS rpm	5600
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	25.4x65.088x22.225
SHOG_yobi	23100R/23256R
Prod_Type3	TRBSR_ID_A
Width (mm)	22,225
Bearing number	23100/23256
Bore Diameter (mm)	25,4
Outer Diameter (mm)	65,088
Calculation factor (e)	0,73

(Oil) Lubrication Speed	8000 r/min
Calculation factor (Y0)	0,45
(Grease) Lubrication Speed	5600 r/min
Basic static load rating (C0)	47,5 kN
Basic dynamic load rating (C)	45 kN