



Bearing No. BTM 100 ATN9/P4CDB

D	150 mm
d	100 mm
H	45 mm
Size (mm)	100x150x45
Width (mm)	45
Mass bearing	2.65 kg
d_n	119.7 mm
d_n	119.7 mm
D_1	137.1 mm
d_1	123 mm
D_1	137.1 mm
d_1	123 mm
Bearing number	BTM 100 ATN9/P4CDB
Preload class A	400 N
G_{ref}	22 cm
Preload class B	1200 N
Bore Diameter (mm)	100
r_b max.	1 mm
r_a max.	1.5 mm
D_a max.	145 mm
d_a min.	107 mm
Outer Diameter (mm)	150
$r_{3,4}$ min.	1 mm
r_a - max.	1.5 mm
D_a - max.	145 mm
$r_{1,2}$ min.	1.5 mm
d_a - min.	107 mm
r_b - max.	1 mm
$r_{3,4}$ - min.	1 mm

$r_{1,2}$ - min.	1.5 mm
Basic dynamic load rating C	41.5 kN
Basic dynamic load rating - C	41.5 kN
Fatigue load limit P_u	3.8 kN
Fatigue load limit - P_u	3.8 kN
Limiting speed for oil lubrication	7900 mm/min
Static axial stiffness for preload A	315 N/ μ m
Static axial stiffness for preload B	476 N/ μ m
Limiting speed for grease lubrication	6300 r/min
Static Axial rigidity, Preload class A	315 N/micron
Basic static load rating C_0	102 kN
Static Axial rigidity, Preload class B	476 N/micron
Attainable speed for grease lubrication	6300 r/min
Basic static load rating - C_0	102 kN
Attainable speed for oil-air lubrication	7900 r/min
Reference grease quantity G_{ref}	22 cm ³