



Bearing No. 23132 CCK/W33 + AH 3132 G

D	270 mm
B	86 mm
b	13.9 mm
K	7.5 mm
G	M 170x3
Size (mm)	270x150x86
Width (mm)	86
$d_2$	184 mm
$G_1$	170 mm
$G_1$	16 mm
$B_1$	103 mm
$d_1$	150 mm
$D_1$	234 mm
$B_1$	103 mm
$d_1$	150 mm
Bearing number	23132 CCK/W33 + AH 3132 G
Limiting speed	2400 r/min
Reference speed	1900 r/min
$D_a$ max.	258 mm
$r_a$ max.	2 mm
$d_a$ min.	168 mm
Bore Diameter (mm)	270
Outer Diameter (mm)	150
$r_a$ - max.	2 mm
Calculation factor e	0.3
$D_a$ - max.	258 mm
$d_a$ - min.	168 mm
$r_{1,2}$ min.	2.1 mm
	108 mm

B <sup>2</sup> ?	
------------------	--

$D_1$ ?	234 mm
$d_2$ ?	184 mm
Mass bearing + sleeve	23 kg
$r_{1,2}$ - min.	2.1 mm
Calculation factor - e	0.3
Basic dynamic load rating C	1029 kN
Basic dynamic load rating - C	1029 kN
Fatigue load limit $P_u$	129 kN
Calculation factor $Y_1$	2.3
Calculation factor $Y_2$	3.4
Calculation factor $Y_0$	2.2
Calculation factor - $Y_2$	3.4
Calculation factor - $Y_1$	2.3
Fatigue load limit - $P_u$	129 kN
Basic static load rating $C_0$	1370 kN
Basic static load rating - $C_0$	1370 kN