



Bearing No. 232/600 CAK/W33 + AOHX 32/600 G

D	1090 mm
B	388 mm
b	22.3 mm
K	12 mm
G	Tr 630x6
Size (mm)	1090x570x388
Width (mm)	388
D ₁	929 mm
G ₁	57 mm
G ₁	57 mm
B ₁	445 mm
d ₁	570 mm
d ₂	754 mm
B ₁	445 mm
B ₂	459 mm
d ₁	570 mm
Bearing number	232/600 CAK/W33 + AOHX 32/600 G
Limiting speed	400 r/min
Reference speed	260 r/min
D _a max.	1050 mm
r _a max.	8 mm
d _a min.	626 mm
Bore Diameter (mm)	1090
Outer Diameter (mm)	570
r _a - max.	8 mm
Calculation factor e	0.35
D _a - max.	1050 mm
d _a - min.	626 mm

$r_{1,2}$ min.	9.5 mm
B_2 ?	459 mm
D_1 ?	929 mm
d_2 ?	754 mm
Mass bearing + sleeve	1760 kg
$r_{1,2}$ - min.	9.5 mm
Calculation factor - e	0.35
Basic dynamic load rating C	15652 kN
Basic dynamic load rating - C	15652 kN
Fatigue load limit P_u	1460 kN
Calculation factor Y_1	1.9
Calculation factor Y_2	2.9
Calculation factor Y_0	1.8
Calculation factor - Y_2	2.9
Calculation factor - Y_1	1.9
Fatigue load limit - P_u	1460 kN
Basic static load rating C_0	25500 kN
Basic static load rating - C_0	25500 kN