



Bearing No. PCZ 9660 E

D	157,163 mm
d	152,4 mm
B	95,25 mm
M	– mm
Weight	0,84 Kg
c1 min	0,2 mm
c2 min	1,2 mm
Size (mm)	152.4x157.163x95.25
Width (mm)	95,25
Mass bushing	0.84 kg
? ±8	20 °
Bearing number	PCZ 9660 E
c ₂ max.	2.4 mm
c ₁ min.	0.2 mm
c ₁ max.	1 mm
c ₂ min.	1.2 mm
Bore Diameter (mm)	152,4
Outer Diameter (mm)	157,163
Housing bore range min.	157.119 mm
Housing bore range max.	157.16 mm
Shaft diameter range min.	152.337 mm
Shaft diameter range max.	152.4 mm
Basic dynamic load rating (C)	1 146 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	1146 kN
Basic static load rating - radial direction C_0	3600 kN
Factor depending on material and bearing type K_M	480