




Bearing No. PCZ 4048 E

D	68,263 mm
d	63,5 mm
B	76,2 mm
M	– mm
Weight	0,285 Kg
c1 min	0,2 mm
c2 min	1,2 mm
Size (mm)	63.5x68.263x76.2
Width (mm)	76,2
Mass bushing	0.28 kg
? ±8	20 °
Bearing number	PCZ 4048 E
c ₂ max.	2.4 mm
c ₁ min.	0.2 mm
c ₁ max.	1 mm
c ₂ min.	1.2 mm
Bore Diameter (mm)	63,5
Outer Diameter (mm)	68,263
Housing bore range min.	68.247 mm
Housing bore range max.	68.278 mm
Shaft diameter range min.	63.482 mm
Shaft diameter range max.	63.528 mm
Basic dynamic load rating (C)	380 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	380 kN
Basic static load rating - radial direction C_0	1200 kN
Factor depending on material and bearing type K_M	480