



Bearing No. 23252 CCK/W33 + AOH 2352 G

D	480 mm
B	174 mm
b	22.3 mm
K	12 mm
G	Tr 280x4
Size (mm)	480x240x174
Width (mm)	174
D <sub>1</sub>	408 mm
G <sub>1</sub>	30 mm
G <sub>1</sub>	30 mm
B <sub>1</sub>	205 mm
d <sub>1</sub>	240 mm
d <sub>2</sub>	312 mm
B <sub>1</sub>	205 mm
B <sub>2</sub>	213 mm
d <sub>1</sub>	240 mm
Bearing number	23252 CCK/W33 + AOH 2352 G
Limiting speed	1200 r/min
Reference speed	850 r/min
D <sub>a</sub> max.	460 mm
r <sub>a</sub> max.	4 mm
d <sub>a</sub> min.	271 mm
Bore Diameter (mm)	480
Outer Diameter (mm)	240
r <sub>a</sub> - max.	4 mm
Calculation factor e	0.35
D <sub>a</sub> - max.	460 mm
d <sub>a</sub> - min.	271 mm

$r_{1,2}$ min.	5 mm
$B_2$ ?	213 mm
$D_1$ ?	408 mm
$d_2$ ?	312 mm
Mass bearing + sleeve	155 kg
$r_{1,2}$ - min.	5 mm
Calculation factor - e	0.35
Basic dynamic load rating C	3395 kN
Basic dynamic load rating - C	3395 kN
Fatigue load limit $P_u$	360 kN
Calculation factor $Y_1$	1.9
Calculation factor $Y_2$	2.9
Calculation factor $Y_0$	1.8
Calculation factor - $Y_2$	2.9
Calculation factor - $Y_1$	1.9
Fatigue load limit - $P_u$	360 kN
Basic static load rating $C_0$	4750 kN
Basic static load rating - $C_0$	4750 kN