



Bearing No. 23276 CAK/W33 + AOH 3276 G

D	680 mm
B	240 mm
b	22.3 mm
K	12 mm
G	Tr 400x5
Size (mm)	680x360x240
Width (mm)	240
d ₂	473 mm
G ₁	400 mm
G ₁	42 mm
B ₁	284 mm
d ₁	360 mm
D ₁	581 mm
B ₁	284 mm
d ₁	360 mm
Bearing number	23276 CAK/W33 + AOH 3276 G
Limiting speed	750 r/min
Reference speed	500 r/min
D _a max.	654 mm
r _a max.	5 mm
d _a min.	396 mm
Bore Diameter (mm)	680
Outer Diameter (mm)	360
r _a - max.	5 mm
Calculation factor e	0.35
D _a - max.	654 mm
d _a - min.	396 mm
r _{1,2} min.	6 mm
	294 mm

B² ?

D_1 ?	581 mm
d_2 ?	473 mm
Mass bearing + sleeve	390 kg
$r_{1,2}$ - min.	6 mm
Calculation factor - e	0.35
Basic dynamic load rating C	6126 kN
Basic dynamic load rating - C	6126 kN
Fatigue load limit P_u	620 kN
Calculation factor Y_1	1.9
Calculation factor Y_2	2.9
Calculation factor Y_0	1.8
Calculation factor - Y_2	2.9
Calculation factor - Y_1	1.9
Fatigue load limit - P_u	620 kN
Basic static load rating C_0	9150 kN
Basic static load rating - C_0	9150 kN