



Bearing No. 23284 CAK/W33 + AOH 3284 G

D	760 mm
B	272 mm
b	22.3 mm
K	12 mm
G	Tr 440x5
Size (mm)	760x400x272
Width (mm)	272
d ₂	526 mm
G ₁	440 mm
G ₁	46 mm
B ₁	321 mm
d ₁	400 mm
D ₁	649 mm
B ₁	321 mm
d ₁	400 mm
Bearing number	23284 CAK/W33 + AOH 3284 G
Limiting speed	630 r/min
Reference speed	450 r/min
D _a max.	728 mm
r _a max.	6 mm
d _a min.	440 mm
Bore Diameter (mm)	760
Outer Diameter (mm)	400
r _a - max.	6 mm
Calculation factor e	0.35
D _a - max.	728 mm
d _a - min.	440 mm
r _{1,2} min.	7.5 mm
	331 mm

B² ?

D_1 ?	649 mm
d_2 ?	526 mm
Mass bearing + sleeve	550 kg
$r_{1,2}$ - min.	7.5 mm
Calculation factor - e	0.35
Basic dynamic load rating C	7677 kN
Basic dynamic load rating - C	7677 kN
Fatigue load limit P_u	765 kN
Calculation factor Y_1	1.9
Calculation factor Y_2	2.9
Calculation factor Y_0	1.8
Calculation factor - Y_2	2.9
Calculation factor - Y_1	1.9
Fatigue load limit - P_u	765 kN
Basic static load rating C_0	11600 kN
Basic static load rating - C_0	11600 kN