



Bearing No. 24056 CCK30/W33 + AOH 24056 G

D	420 mm
B	140 mm
b	11.1 mm
K	6 mm
G	Tr 300x4
Size (mm)	420x260x140
Width (mm)	140
d ₂	309 mm
G ₁	300 mm
G ₁	22 mm
B ₁	162 mm
d ₁	260 mm
D ₁	368 mm
B ₁	162 mm
d ₁	260 mm
Bearing number	24056 CCK30/W33 + AOH 24056 G
Limiting speed	1400 r/min
Reference speed	950 r/min
D _a max.	405 mm
r _a max.	3 mm
d _a min.	287 mm
Bore Diameter (mm)	420
Outer Diameter (mm)	260
r _a - max.	3 mm
Calculation factor e	0.31
D _a - max.	405 mm
d _a - min.	287 mm
r _{1,2} min.	4 mm
	179 mm

B ² ?	
------------------	--

D_1 ?	368 mm
d_2 ?	309 mm
Mass bearing + sleeve	79 kg
$r_{1,2}$ - min.	4 mm
Calculation factor - e	0.31
Basic dynamic load rating C	2248 kN
Basic dynamic load rating - C	2248 kN
Fatigue load limit P_u	285 kN
Calculation factor Y_1	2.2
Calculation factor Y_2	3.3
Calculation factor Y_0	2.2
Calculation factor - Y_2	3.3
Calculation factor - Y_1	2.2
Fatigue load limit - P_u	285 kN
Basic static load rating C_0	3800 kN
Basic static load rating - C_0	3800 kN