



Bearing No. PCZ 2228 E

D	38,894 mm
d	34,925 mm
B	44,45 mm
M	– mm
Weight	0,077 Kg
c1 min	0,1 mm
c2 min	0,8 mm
Size (mm)	34.925x38.894x44.45
Width (mm)	44,45
Mass bushing	0.077 kg
? ±8	20 °
Bearing number	PCZ 2228 E
c ₂ max.	1.6 mm
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.8 mm
Bore Diameter (mm)	34,925
Outer Diameter (mm)	38,894
Housing bore range min.	38.882 mm
Housing bore range max.	38.908 mm
Shaft diameter range min.	34.854 mm
Shaft diameter range max.	34.895 mm
Basic dynamic load rating (C)	122 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	122 kN
Basic static load rating - radial direction C_0	380 kN
Factor depending on material and bearing type K_M	480