



Bearing No. BK2216

	IR17X22X16 / Suitable inner ring
D	28 mm
m	24 g / Weight
Noun	Bearing
Bore	0.866 Inch 22 Millimeter
Width	0.63 Inch 16 Millimeter
UNSPSC	31171512
Category	Needle Non Thrust Roller Bearing
Retainer	Yes
Component	Roller Assembly with Outer Ring - No Inner Ring
Size (mm)	22x28x16
Inventory	0.0
Enclosure	Open
Separable	No
Width (mm)	16
Closed End	Yes
Weight / LBS	0.046
Self Aligning	No
Product Group	B04144
n_B	8000 1/min / Reference speed
Inch - Metric	Metric
n_G	11700 1/min / Limiting speed
C_r	13400 N / Dynamic load rating (radial)
F_w	22 mm

Other Features	1 Rib Outer Ring Drawn Cup Bearing Steel Cage
Thrust Bearing	No
C_{ur}	2800 N / Fatigue limit load, radial
C_{Or}	22100 N / Static load rating (radial)
Keyword String	Needle
Relubricatable	No
Bearing number	BK2216
Rolling Element	Needle Roller Bearing
r_{min}	0,8 mm
Long Description	22MM Bore; 28MM Outside Diameter; 16MM Width; Needle Roller Bearing; Roller Assembly with Outer Ring - No Inner Ring; Open Enclosure; No Self Aligning; Retainer; Single Row of Rollers; No Separable; C
Manufacturer URL	http://www.ina.com
Outside Diameter	1.102 Inch 28 Millimeter
Weight / Kilogram	0.02
Manufacturer Name	SCHAEFFLER GROUP
$C_{t min}$	13,3 mm
Bore Diameter (mm)	22
Outer Diameter (mm)	28
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	BK2216
Number of Rows of Rollers	Single Row

C - 16 mm / Tolerance: -0,3	16 mm / Tolerance: 0,3
--------------------------------	------------------------