



Bearing No. 51336X

| | |
|--------|---------|
| C | 480 |
| r | 3 |
| d | 180 mm |
| D | 300 mm |
| T | 95 mm |
| Z_ | 16 |
| ra | 2.5 |
| D_ | 300 |
| C0 | 1680 |
| da | 251 |
| B_ | 95 |
| D1 | 184 mm |
| d1 | 295 mm |
| T_ | 95 |
| SRE | 22.3 |
| D_1 | 184 |
| SRI | 22.3 |
| D_a | 229 |
| DA_ | 41.275 |
| yobi | 51336X |
| SREN | 0 |
| SRIN | 0 |
| SRIX | 0.16 |
| SDM_ | 240 |
| mass | 25.9 |
| KBRG | 5111 |
| SREX | 0.16 |
| Weight | 25,9 Kg |
| r min. | 3 mm |
| LangID | 1 |

| | |
|-------------------------------|-------------|
| ra max. | 2,5 mm |
| da min. | 251 mm |
| Da max. | 229 mm |
| Oil rpm | 850 |
| GRS rpm | 560 |
| hidYobi | 51336X |
| hidTable | ecat_NSSDTB |
| Size (mm) | 180x300x95 |
| Prod_Type3 | TB_SD_WFS |
| Width (mm) | 95 |
| Bearing number | 51336X |
| Bore Diameter (mm) | 180 |
| Outer Diameter (mm) | 300 |
| (Grease) Lubrication Speed | 560 r/min |
| Basic static load rating (C0) | 1680 kN |
| Basic dynamic load rating (C) | 480 kN |