




Bearing No. PCZ 1216 M

D	22,225 mm
d	19.05 mm
B	25,4 mm
M	3 mm
Weight	0,017 Kg
c1 min	0,1 mm
c2 min	0,2 mm
Size (mm)	19.05x22.225x25.4
Width (mm)	25,4
Mass bushing	0.017 kg
? ±8	20 °
Bearing number	PCZ 1216 M
c ₂ max.	1 mm
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.2 mm
Bore Diameter (mm)	19.05
Outer Diameter (mm)	22,225
Housing bore range min.	22.225 mm
Housing bore range max.	22.245 mm
Shaft diameter range min.	18.74 mm
Shaft diameter range max.	18.771 mm
Basic dynamic load rating (C)	56 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	56 kN
Basic static load rating - radial direction C_0	118 kN
Factor depending on material and bearing type K_M	1900