



Bearing No. PCZ 0908 M

D	16,669 mm
d	14,288 mm
B	12,7 mm
M	3 mm
Weight	0,0044 Kg
c1 min	0,1 mm
c2 min	0,2 mm
Size (mm)	14.288x16.669x12.7
Width (mm)	12,7
Mass bushing	0.0044 kg
? ±8	20 °
Bearing number	PCZ 0908 M
c ₂ max.	1 mm
c ₁ min.	0.1 mm
c ₁ max.	0.6 mm
c ₂ min.	0.2 mm
Bore Diameter (mm)	14,288
Outer Diameter (mm)	16,669
Housing bore range min.	16.667 mm
Housing bore range max.	16.685 mm
Shaft diameter range min.	14 mm
Shaft diameter range max.	14.026 mm
Basic dynamic load rating (C)	21,6 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	21.6 kN
Basic static load rating - radial direction C_0	45.5 kN
Factor depending on material and bearing type K_M	1900