



Bearing No. PCZ 0912 E

D	16,669 mm
d	14,288 mm
B	19,05 mm
M	– mm
Weight	0,0082 Kg
c1 min	0,1 mm
c2 min	0,2 mm
Size (mm)	14.288x16.669x19.05
Width (mm)	19,05
Mass bushing	0.0082 kg
? ±8	20 °
Bearing number	PCZ 0912 E
c ₂ max.	1 mm
c ₁ min.	0.1 mm
c ₁ max.	0.6 mm
c ₂ min.	0.2 mm
Bore Diameter (mm)	14,288
Outer Diameter (mm)	16,669
Housing bore range min.	16.66 mm
Housing bore range max.	16.678 mm
Shaft diameter range min.	14.237 mm
Shaft diameter range max.	14.262 mm
Basic dynamic load rating (C)	21,6 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	21.6 kN
Basic static load rating - radial direction C_0	68 kN
Factor depending on material and bearing type K_M	480