



Bearing No. PCZ 1010 E

D	18,256 mm
d	15,875 mm
B	15,875 mm
M	– mm
Weight	0,0075 Kg
c1 min	0,1 mm
c2 min	0,2 mm
Size (mm)	15.875x18.256x15.875
Width (mm)	15,875
Mass bushing	0.0075 kg
? ±8	20 °
Bearing number	PCZ 1010 E
c ₂ max.	1 mm
c ₁ min.	0.1 mm
c ₁ max.	0.6 mm
c ₂ min.	0.2 mm
Bore Diameter (mm)	15,875
Outer Diameter (mm)	18,256
Housing bore range min.	18.247 mm
Housing bore range max.	18.268 mm
Shaft diameter range min.	15.824 mm
Shaft diameter range max.	15.85 mm
Basic dynamic load rating (C)	20 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	20 kN
Basic static load rating - radial direction C_0	63 kN
Factor depending on material and bearing type K_M	480