



Bearing No. PCZ 0606 M

D	11,906 mm
d	9,525 mm
B	9,525 mm
M	– mm
Weight	0,0023 Kg
c1 min	0,1 mm
c2 min	0,2 mm
Size (mm)	9.525x11.906x9.525
Width (mm)	9,525
Mass bushing	0.0023 kg
? ±8	20 °
Bearing number	PCZ 0606 M
c ₂ max.	1 mm
c ₁ min.	0.1 mm
c ₁ max.	0.6 mm
c ₂ min.	0.2 mm
Bore Diameter (mm)	9,525
Outer Diameter (mm)	11,906
Housing bore range min.	11.905 mm
Housing bore range max.	11.923 mm
Shaft diameter range min.	9.243 mm
Shaft diameter range max.	9.266 mm
Basic dynamic load rating (C)	10,8 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	10.8 kN
Basic static load rating - radial direction C_0	22.8 kN
Factor depending on material and bearing type K_M	1900