



Bearing No. PWKRE 47.2RS

G	M 20x1.5
C	24 mm
c	1 mm
M	6 mm
D	47 mm
d	24 mm
B	66 mm
SW	10 mm
Category	Bearings
Inventory	0.0
Size (mm)	24x47x66
Width (mm)	66
B ₁	40.5 mm
d ₁	27 mm
Product Group	B04144
B ₁	40.5 mm
B ₂	9 mm
B ₃	18 mm
C ₁	0.8 mm
M ₁	4 mm
B ₂	9 mm
G ₁	21 mm
M ₁	4 mm
G ₁	21 mm
Hexagonal nut	M 20x1.5
d ₁	27 mm
C ₁	0.8 mm
B ₃	18 mm
Bearing number	PWKRE 47.2RS

Limiting speed	3800 r/min
Grease fitting	NIP A2x7.5
Mass cam follower	0.4 kg
Manufacturer Name	SKF
Weight / Kilogram	0
Bore Diameter (mm)	24
Outer Diameter (mm)	47
Lubrication adapter	AP 10
Mass support roller	0.4 kg
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	1 mm
$r_{1,2}$ - min.	1 mm
Basic dynamic load rating C	22.9 kN
Basic dynamic load rating - C	22.9 kN
Recommended tightening torque	120 N·m
Fatigue load limit P_u	2.8 kN
Fatigue load limit - P_u	2.8 kN
Basic static load rating C_0	24.5 kN
Basic static load rating - C_0	24.5 kN
Maximum dynamic radial loads - F_r	18.3 kN
Maximum static radial loads - F_{0r}	26 kN
Maximum dynamic radial loads F_r max.	18.3 kN
Maximum static radial loads F_{0r} max.	26 kN